

## Filter Cartridge Selection Guide

### Tab 1 Hurricane® Cartridges

- ▶ High flow, high surface area
- ▶ Low initial pressure drop provides longer filter life
- ▶ NSF-61 Listed cartridges available
- ▶ High Temperature cartridges available
- ▶ Lowest cost per filtered gallon based on surface area



### Tab 2 Premium & WaterBetter®

- ▶ 2-1/2" and 2-3/4" O.D. pleated cartridges designed for Harmsco® HIF, Band Clamp and competitive filter housings
- ▶ NSF-61 Listed
- ▶ All cartridges shrink wrapped
- ▶ Available in 9-3/4", 10", 20", 30" and 40" cartridge lengths



### Tab 3 701 Series Cartridges

- ▶ 2-1/2" O.D. pleated cartridges designed for Harmsco® and competitive filter housings
- ▶ NSF-61 Listed
- ▶ All cartridges shrink wrapped
- ▶ 9-3/4", 10", 20", 30" and 40" lengths; Polyester, Harmsco-Free™ and Poly-Pleat™ media



### Tab 4 Calypso Blue™ Cartridges

- ▶ 4-1/2" O.D. pleated cartridges designed for Harmsco® HIF, Band Clamp and single cartridge housings
- ▶ Premium Series offers up to 12 sq.ft. of media per 9-3/4" length; WaterBetter® Series 9.5 sq. ft.
- ▶ NSF-61 Listed
- ▶ All cartridges shrink wrapped



### Tab 5 SureSafe™ Cartridges

- ▶ Antimicrobial cartridge media prohibits growth of bacteria and mold on filter cartridge
- ▶ Offered in 20 and 50 micron ratings and a wide range of cartridge sizes
- ▶ Agion Silver Zeolite is FDA tested and registered with the EPA



### Tab 6 Poly-Pleat™ Cartridges

- ▶ Pleated one micron absolute cartridges for safe, cyst-free drinking water
- ▶ NSF-61 Listed
- ▶ Available in a wide range of cartridge sizes



### Tab 7 Carbon Cartridges

- ▶ Hurricane®, HAC and WaterBetter® Carbon cartridges for high chlorine, taste, odor, lead, THM and organic chemical removal
- ▶ Available in a wide range of cartridge sizes, including Hurricane® 170 Series
- ▶ NSF-42 Listed



### Tab 8 All Poly/High Purity

- ▶ Available in: Polypropylene - PP; Polyethersulfone - PES Membrane; Microfiberglass - FG; Nylon 6,6 - NY and Plus + Nylon 6,6 - NYP; Teflon - TF Membrane
- ▶ Available in DOE, 222 w/Fin, 222 w/Flat Cap, 226 w/Flat Cap, 226 w/Fin, 213 Internal O-Ring
- ▶ Available in Hurricane® sizes 40, 90, 170 and 0.2, 0.45, 1, 5, 10, 20, 50 micron ratings.



### Tab 9 High Temperature

- ▶ Pleated polyester or cellulose phenolic media
- ▶ Two temperature ratings to choose from: 200°F (93°C) and 250°F (121°C)
- ▶ Designed for Hurricane® and WaterBetter® housings



### Tab 10 Liquid Filter Bags

- ▶ "V" Seal Ring Bags available to prevent by-pass
- ▶ Polypropylene and Polyester options available
- ▶ Broad chemical compatibility
- ▶ Industry #1, #2 and EXT extended bag sizes available



### Tab 11 NSF Certified

**Note:** This publication is to be used as a guide. The data within has been obtained from many sources and is considered to be accurate. Harmsco does not assume liability for the accuracy and/or completeness of this data. Changes to the data can be made without notification. Temperature, Pressure, Flow Rates, Differential Pressures, Chemical Combinations and other unknown factors can affect performance in unknown ways. **Limited Warranty:** Harmsco warrants their products to be free of material and workmanship defects. Determination of suitability of Harmsco products for uses and applications contemplated by Buyer shall be the sole responsibility of Buyer. The end user/installer/buyer shall be liable for the product's performance and suitability regarding their specific intended applications. End users should perform their own tests to determine suitability for each application.