

All-Poly Absolute Rated

99.98 Efficiency (Beta 5000)

Pleated Polypropylene Cartridges

Harmsco® High Purity Pleated Cartridges are manufactured for use in applications where absolute rated filtration is needed.


Long service life
High flow rates
Low pressure drop
High permeability

Features

- ▶ Cartridge Assembly Materials are 100% polypropylene; avoids leaching or contamination
- ▶ High efficiency for critical filtration applications
- ▶ Pleated design for extended surface area
- ▶ Thermally bonded structure
- ▶ USP Class VI - 121°C (250°F) for plastics
- ▶ Offered in multiple lengths and end cap configurations to fit in most filter housings
- ▶ FDA Listed Materials: Manufactured from materials which are listed for food contact applications in Title 21 of the U.S. Code of Federal Regulations

Applications

- ▶ Food & Beverage
- ▶ Cosmetics
- ▶ Photographic Solutions
- ▶ Reagent and Electronic Grade Chemicals
- ▶ Bottled Water
- ▶ Prefiltration Prior To Membrane Filters
- ▶ DI and RO Feedwater Prefiltration
- ▶ Magnetic Media Chemicals
- ▶ Process Water
- ▶ Fine Chemicals
- ▶ Plating Chemicals
- ▶ Wastewater
- ▶ Pharmaceuticals and Biologicals
- ▶ Ophthalmics



Pleated Polypropylene Cartridges



Specifications

Construction Materials

Membrane Polypropylene
 Support Media Polypropylene
 End Caps Polypropylene
 Center Core Polypropylene
 Outer Support Cage Polypropylene
 O-rings/Gaskets Buna, Viton, EPDM,
 Silicone, Teflon® Encapsulated Viton

Toxicity

All components meet the specifications for biological safety per USP Class VI: 250°F (121°C) for plastics.

Dimensions

Length: 10 to 40 inches (25.4 to 101.6 cm) nominal
 Outside Diameter: 2.7 inches (7.0 cm) nominal

Maximum Recommended Operating Conditions

Change Out ΔP 35 psi
 Temperature 180°F (82°C)

Maximum Differential Pressure

60 psid (4.1 bar) at 68°F (20°C)

FDA Listed Materials

Manufactured from materials which are listed for food contact applications in Title 21 of the U.S. Code of Federal Regulations.

Sanitization/Sterilization

Filtered Hot Water 194°F (90°C)

Chemical Sanitization - Industry standard concentrations of hydrogen peroxide, peracetic acid, sodium hypochlorite and other selected chemicals.

Cartridge Selection/Sizing Guide


Packed 12 per case, with cartridges individually bagged and cartoned.

Model	Length	Micron Size	End Cap Code	O-Rings/Gaskets	Options
PP	975 (9-3/4")	0.2	DOE (double open end)	E (EPDM)*	I (stainless steel insert)
	195 (19-1/2")	0.45	213 (internal o-ring)	B (Buna)	HP (heavy poly core)
	20 (20")	1	222 (flat cap)	S (Silicone)	
	2925 (29-1/4")	5	222-F (fin)	V (Viton)	
	30 (30")	10	222-S (spring)	T (Teflon Encapsulated Viton)	
	40 (40")	20	226 (flat cap)		
		40	226-F (fin)		
			226-S (spring)		

Example: PP – 195 – 0.2 – 222-F – E

EPDM is standard for all o-rings and gaskets, unless otherwise noted.

Flow Rate



Cartridge End Cap Configurations



Note: This publication is to be used as a guide. The data within has been obtained from many sources and is considered to be accurate. Harmsco does not assume liability for the accuracy and/or completeness of this data. Changes to the data can be made without notification. Temperature, Pressure, Flow Rates, Differential Pressures, Chemical Combinations and other unknown factors can affect performance in unknown ways. **Limited Warranty:** Harmsco warrants their products to be free of material and workmanship defects. Determination of suitability of Harmsco products for uses and applications contemplated by Buyer shall be the sole responsibility of Buyer. The end user/installer/buyer shall be liable for the product's performance and suitability regarding their specific intended applications. End users should perform their own tests to determine suitability for each application.



HARMSCO® Filtration Products

7169 49th Terrace North, Riviera Beach, FL 33407
 (561) 848-9628 • Toll-free: (800) 327-3248 • E-mail: sales@harmsco.com

www.harmsco.com



Made in USA
 3/26 Rev. 2